

A large orange riding lawn mower is shown in the background of the top half of the page. It has a black seat, a steering wheel, and large black tires. The mower is parked on a green lawn.

# UFA 2-CYCLE ENGINE OIL

## premium QUALITY

UFA premium Two-Cycle Engine Oil is formulated to provide optimal lubrication and wear protection to meet or exceed requirements for today's conventional and direct fuel injection (DFI) two cycle engines. It has been enhanced with a specialty additive package that offers added lubricity and extended engine life while protecting against excessive wear and deposit formation.

## product APPLICATION

- For use in conventional and direct fuel injection (DFI) two cycle engines as set forth by the most current National Marine Manufacturers Association (NMMA) TC-W3 service classification and exceeds the requirements of API TC.
- Recommended for outboard motors, personal watercraft, snowmobiles, motorcycles requiring API TC performance, chain saws, golf carts and lawn mowers.





## performance **BENEFITS**

- Formulated with a specialty additive package to offer added lubricity and extended engine life.
- Oil is dyed blue for easy visual recognition.
- Manufactured with an ashless formulation with high quality components making the exhaust nearly smokeless.

## typical **PROPERTIES**

### ISO Viscosity Grade

Kinematic Viscosity	
100°C, cSt (ASTM D-445)	7.3
40°C, cSt (ASTM D-445)	45.5
Viscosity Index (ASTM D-2270)	128
Zinc (wt%)	0
Calcium (wt%)	0
Phosphorus (wt%)	0
Sulfur (wt%)	0
Barium (wt%)	0
Sulfated Ash (wt%)	0
Flash Point oC	>93.3
Pour Point oC (ASTM D-6749)	-45
Specific Gravity	0.871
API Gravity (ASTM D-1298)	30.9

\*Values shown here are typical and may vary

## available **SIZES**

### CASES

### ARTICLE #

12 x 946 mL

1123954

For additional information, please contact your local UFA Petroleum agent or Petroleum Sales Representative.